



Face protection that enables the wearer to work on or be in the vicinity of live electric parts with Class 2 arc flash protection (According to GS-ET-29). Recommended for use with balaclava. Securely flips up and down. Tested and approved in combination with the Zenith and Zenith X helmet, by attaching directly to the Visor Attachment Slots.

TECHNICAL DETAILS



MATERIAL
Polycarbonate
Clear - 1 mm thick



STANDARD
EN166
EN170
DGVU GS ET29 - Class 2
ANSI Z87.1 + ASTM F2178



OPTICAL CLASS
1



CATEGORY
III



WEIGHT
425 g



ATPV
12 cal/cm²

TECHNOLOGIES



ANTI-FOG
Equipped with an anti-fog treatment to increase wearer visibility when active and in a variety of conditions.



DRIP PROOF UPPER CONTOUR
Designed with a rubber upper contour to keep out sweat moisture and to enhance comfort.



> CRI 95
Designed with excellent Color Rendering Index performance for greater color contrast and visibility.



SEE-THROUGH CHIN PROTECTION
Equipped with transparent chin protection for enhanced range of worksite visibility.



PANORAMIC LENS
Wide view lens for optimal protection and visibility.



SCRATCH RESISTANT
Equipped with a scratch-resistant treatment for increased durability.



COMPATIBLE WITH GLASSES
Designed for use over corrective glasses.



STABLE CARRIER
Provided with carrier for use with helmet.

MARKINGS

CODE **MARKING**

WVI00015- | **KASK** | ⚡ 1000 V | CE 1883 | 2C - 1,2 | 1 | B | 8 | 1 | 3 | ATPV 12.0 cal/cm²

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

3 **10**
YEARS **YEARS**
GUARANTEE **SHELF LIFE**

SHELF LIFE

10 years starting from the date of manufacture. Shelf life depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

CLEANING

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor. Do not rub the lens when dry.

ARC FLASH VISOR COLLECTION



WVI00014
ARC FLASH VISOR 1



WVI00015
ARC FLASH VISOR 2

DISCOVER MORE



SCAN FOR
COMPLETE
COLLECTION